

Yamaha Waverunner Winterization Checklist

By: JetSkiExperts

Position Yamaha wave runner so that it is tilted for draining (bow higher than stern)

Remove drain plugs to empty the hull

You can turn on the wave runner and give the throttle short bursts, which will drain all of the water. Be sure to only turn the throttle in 30-second intervals to prevent overheating.

Remove spark plugs one at a time and spray fogging oil into each cylinder. Start the Waverunner after each cylinder to circulate.

Wash engine compartment thoroughly with soap and water

Ensure hull has completely drained

Replace drain plugs

Mix Antifreeze in the bucket with water - 1:1 ratio

Flush antifreeze mixture through the exhaust system

Add fuel stabilizer to the gas tank

Fill the gas tank completely full with premium gasoline

Wash exterior of jet ski

Rinse and dry Waverunner

Wax your Yamaha Waverunner so that it looks beautiful and shiny

Lubricate the control cables with silicone lubricant

Lubricate the steering system

Apply a thin coat of lubricant spray into the engine

Yamaha Waverunner Winterization Checklist

By: JetSkiExperts

- Lubricate any other moving parts
- Remove the battery
- Charge the battery completely with automatic charger
- Store battery in a dry place with mild temperatures
- Prepare for storage. Do not keep the seat completely latched shut. This will prevent mildew from any remaining moisture
- Cover your Yamaha Waverunner and move to a garage or storage unit.